N 50 BUILT-IN/-UNDER EL. DOUBLE OVEN/COOKER J1ACE4HNOB BLACK





Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11TI15X0 Cliprails



Built under double oven - twice as flexible, twice as fast - bake or roast multiple dishes at the same time.

- $\sqrt{\mbox{ CircoTherm}^{\mbox{\scriptsize @}}}$ the unique hot air-system for simultaneous baking and roasting on up to 3 levels
- $\sqrt{\mbox{ EasyClean}^{\mbox{\tiny @}}}$ this special cleaning aid provides uncomplicated, energy-saving cleaning of the oven interior.
- $\sqrt{\ }$ An environment-saving option for fast oven cleaning.
- $\sqrt{\ }$ Clip-on Rail easily removed and installed telescopic rails for flexible use on all shelf levels

Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in Integrated Cleaning system: No

Dimensions of the product (mm) : $717 \times 594 \times 550$

Dimensions of the packed product (HxWxD) (mm) : $790 \times 690 \times 660$

Control Panel Material: Glass Door Material : Glass Net weight (kg): 48.5 Usable volume of cavity (I): 47

Cooking method: Bottom heat, Conventional heat, Full width grill,

Heißluft sanft, Hot Air, Hot air grilling, Pizza setting Temperature control: No control of the temperature

Number of interior lights: 1 Approval certificates: CE, VDE EAN code: 4242004222002 Energy efficiency class (2010/30/EC): A

Energy consumption per cycle conventional (2010/30/EC): 0.84 Energy consumption per cycle forced air convection (2010/30/EC) :

Energy efficiency class (2010/30/EC) - cavity 2 : B

Energy consumption per cycle conventional - cavity 2 (2010/30/EC) :

Energy efficiency index (2010/30/EC): 94.7

Energy efficiency index cavity 2 (2010/30/EC): 120.3

Electrical connection rating (W): 5300

Current (A): 25 Voltage (V): 220-240 Frequency (Hz): 50

Plug type: fixed connection, no plug



N 50 BUILT-IN/-UNDER EL. DOUBLE OVEN/COOKER J1ACE4HNOB BLACK

Feature:

Design

- Retractable control dials
- Bar handle

Main Lower oven

- Oven capacity: 47 litre
- 1 Clip rail, Stop function
- Heating up indicator
- Control panel lock
- Smooth cavity interior, Shelf support rails
- Cavity (inner surface) bottom: Enamel grey
- Interior halogen light

Programmes/functions

- 7 heating methods: CircoTherm®, Top/bottom heat, Hot air grilling, Full surface grill, CircoTherm® intensive, Bottom heat, CircoTherm® gentle
- Manual rapid heating up

Cleaning

- EcoClean Direct : back panel
- EasyClean
- Full glass inner door

Secondary top oven

- Cavity volume: 34 Litre
- Interior halogen light
- Cavity (inner surface) top: Enamel grey

Programmes/functions

 Oven with 4 heating methods: Top/bottom heat, Full surface grill, Small area grill, Bottom heat

Cleaning

• EcoClean Direct :ceiling, side liners, back panel

Standard accessories

- 2 x combination grid, 1 x universal pan
- 1 Clip rail, Stop function

Performance/technical information

Energy efficiency rating (acc. EU Nr. 65/2014): A
 Energy consumption per cycle in conventional mode: 0.84 kwh
 Energy consumption per cycle in fan-forced convection mode: 0.71 kwh

Number of cavities: 1 Heat source: electrical Cavity volume: 47 litre

• Energy efficiency rating (acc. EU Nr. 65/2014): B

Energy consumption per cycle conventional mode: 0.83 kwh

Number of cavities: 2 Heat source: electrical Cavity volume: 34 Litre • Nominal voltage: 220 - 240 V


Norminal voltage. 220 - 240 v

• Appliance dimension (hxwxd): 717 mm x 594 mm x 550 mm

 \bullet Please refer to the dimensions provided in the installation manual

N 50 BUILT-IN/-UNDER EL. DOUBLE OVEN/COOKER J1ACE4HNOB BLACK

Dimensioned drawings



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	39 mm	40 mm
Full surface induction hob	49 mm	50 mm
Gas hob	29 mm	36 mm
Electric hob	29 mm	32 mm